Quality Water Treatment
Water Softeners and Filtration Systems for Home and Business

FilterSorb SP
Installation, Maintenance, and Service Manual:

100% Scale Removal For Pipes and Hardware
Scale Prevention
No Backwash
No Chemicals
Highly Efficient
High Flow Rates 15 gallons per minute
Long Lifetime

Contact Time: 9 Seconds
Ph Range: 6.5 – 11
Temperature (raw water): Not Limited
Chlorine Content: <3 ppm
The water must be free from oil and grease.
Fe, Mn and H2S Pre-filtration Required.

1). Place the FilterSorb SP system in the desired location.

2). Use the funnel to add the media, unplug tube in tank after adding media.

3). Snap cone shaped basket into bottom of valve. and screw valve onto tank.

4). Attach carbon filter housing to the upflow side of FilterSorb valve on tank then bring main line into carbon filter housing.

5). Turn water on slowly and run water through system into a bucket until water runs smoothly into bucket = no air a steady stream of water.

6).Attach line to house using flow valve with arrow facing towards house.

7). That is it.

Copyright © 2007 Quality Water Treatment, All right reserved.

Make sure you cut all detergents and soap down to 50% and use a dish washing detergent low in Phosphates. You may also have to use Jet Dry until the calcium build up is gone in the dishwasher.

Our 90 day Guarantee:

Being we sell Conventional Water Softeners as well we have a guarantee that no one else can match.

If you are not satisfied with your FilterSorb SP systems performance after 90 days of use, simply call us for a return authorization number. We will then give you the return address to ship your system back and you have a choice of either purchasing a conventional water softener from us and we will credit you the difference or you can just return it for a full refund less return freight charges. System must be in good condition when received.

Quality Water Treatment
1-866-278-4130

Copyright © 2007 Quality Water Treatment, All right reserved.