



Quality Water Treatment

Water Softeners and Filtration Systems for Home and Business

Specification for Commercial Clack WS1.5

Model Number	Tank Size		Capacity		Resin Cu Ft	Support Bed		Flow Rates		BKW	Salt Req'd		Space Req'd L x W x H	Shipping Weight
	Resin	Brine	Min	Max		% x %	% x %	Min	Max		10#	15#		
WS1.5-120	16 x 65	24 x 50	96k	120k	4	-	75	20	41	7	40	60	44 x 24 x 75	440
WS1.5-150	18 x 65	24 x 50	120k	150k	5	-	100	25	53	9	50	75	46 x 24 x 78	558
WS1.5-210	21 x 62	24 x 50	168k	210k	7	100	50	35	60	12	70	105	49 x 24 x 74	725
WS1.5-300	24 x 72	30 x 48	240k	300k	10	150	100	40	66	15	100	150	58 x 30 x 81	1054
WS1.5-300	30 x 72	39 x 48	360k	450k	15	250	100	45	66	25	150	225	73 x 39 x 88	1523

• Capacities are based on resin manufacturer's data • All units set at minimum salt settings • When sizing units, use minimum capacity • All flow rates are in Gallons per Minute • All sizes and space required are in inches

1-1/2" Meter Range • Std. Range - 10,625 Gallons • Ext Range - 53,125 Gallons